

Room Requirements

Logitech Rally Bar Videoconferencing Room System

Conference Room

- The conference room should be a fully enclosed space, separate from other spaces within the building
- The conference room should be no larger than 32 feet long and 25 feet wide and no smaller than 10 feet long and 10 feet wide
- If there is equipment located at the conference table and there is no trenched cable path to the table, cabling will be run over-the-floor using over-the-floor cabletrack

Conference Table

- The conference table should be positioned perpendicular to the front wall
- The conference table should be a typical rectangular design. "V" or "U" shaped conference tables will not work for this setup
- The front lip of the conference table should be no less than 4.5 feet away from the front wall and no further than 8 feet from the front wall
- The conference table must have cut outs on the surface for cables to pass through from beneath. If no cut outs are present, cut outs will be made during installation
- The conference table can be no thicker than 1.9 inches (50mm) if using Rally Mic Pod Mount(s)
- If there is no trenched cable path to the table, cabling will be run over-the-floor using over-the-floor cabletrack

Front Wall

- The front wall must be composed of sheetrock, plaster, brick, or concrete (not glass, marble, or tile)
- The front wall must be clear of any obstructions before the installation
- 3/4" plywood backing will be required at the display location for displays 86" or larger. Plywood backing is not included with installation and must be supplied by others
- The conference table must have cut outs on the surface for cables to pass through from beneath. If no cut outs are present, cut outs will be made during installation

Credenza

- The height of the credenza should be no less than 35" and no greater than 47"
- The credenza should be at least 12 inches deep and at least 32" wide